PORT CONNECTOR CABLE F5000-K011

Motherboard Accessories







Optional cable/connector extension offering an additional serial port with limited feature set

- Proprietary 14 pin mainboard connector (female)
- ► Standard 9 pin Sub-D slot bracket connector



► TECHNICAL INFORMATION

PHYSICAL SPECIFICATIONS

Cable length 75 mm Integrated RS-232 signal level converter (transceiver)

OPERATING SYSTEMS

All (no drivers required)

SUPPORTED MOTHERBOARDS D3544-S only

MOTHERBOARD CONNECTOR

MOTHERBOARD PIN #	D-SUB PIN #	SIGNAL	MOTHERBOARD PIN #	D-SUB PIN #	SIGNAL
1		reserved	8		reserved
2		reserved	9	5	GND
3	2	RXD	10		reserved
4	7	RTS	11		reserved
5	3	TXD	12		VCC_Logic
6	8	CTS	13		PWR_OK
7		reserved	14		VCC_3.3 V





Available RS-232 signals via D-Sub connector: RXD/RTS/TXD/CTS/GND (1.8 V; 1.5 mA max.) VCC-Logic (1.8 V), PWR_Ok, and VCC_3.3 V are used for the transceiver integrated in the COM cable

ORDERING INFORMATION

ARTICLE	PART NO.	DESCRIPTION
INTERNAL COM2 PORT CONNECTOR CABLE	F5000-K011	Cable T26139-Y3589-V415 (w/o slot bracket) Mounting screws for D-Sub connector

Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5 86156 Augsburg, Germany Tel.: + 49 821 4086 0 Fax: +49 821 4086 111 info@kontron.com www.kontron.com